

Illustrative render generated from published specifications

18.5 × 65.2 mm

Efest 18650

2100mAh 38A



Live page & updates

Efest · released 2017

18650LMO

MOOCH-TESTED · 38 A

2,100 mAh CAPACITY	38 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	7.56 Wh ENERGY
--	---	---	--------------------------------------

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S

#212 of 279

Lowest in databaseHighest

Higher discharge than 96% of 18650 cells in our database.
Great for high-drain builds.

VOLTAGE OPERATING WINDOW

1.7 V usable

Cutoff 2.5 VNominal 3.6 VMax 4.2 V

Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	Usable for powerwalls but lower capacity means you'll need more cells to hit your target kWh.
Ebike packs	Marginal. Check your motor's peak draw first. You might get voltage sag under load.
Car audio	Enough discharge to handle amplifier bursts without voltage sag.
High-drain vaping	Above the 25A Mooch CDR threshold. Suitable for regulated and mechanical mods.
Flashlights	Lower capacity means shorter runtime. Better cells are available for flashlight use.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY		PHYSICAL	
Manufacturer	Efest	Diameter	18.5 mm
Model	18650 2100mAh 38A	Length	65.2 mm
Format	18650	ELECTRICAL	
Chemistry	LMO		
Year released	2017		
Wrap colour	Purple		
Terminal	Flat top		
Protection	Unprotected	Rated capacity	2,100 mAh
OPERATING TEMPERATURE		Nominal voltage	3.6 V
		Max charge voltage	4.2 V
		Discharge cutoff	2.5 V
		Energy	7.56 Wh
		Internal resistance	20 mΩ
Charging	0°C to 45°C	Max continuous discharge	38 A (mooch)
Discharging	-20°C to 75°C	Discharge C-rate	18.1C
ENERGY & POWER DENSITY		Standard charge current	2,000 mA
		Typical charge time	1.1 h
		Energy	7.56 Wh
		Volumetric density	431.36 Wh/L
		Power density (volume)	7,806 W/L
Capacity ranking	#212 of 279 18650s		

C-RATE CONVERSION · 2,100 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.42 A	5h 00m
0.5C	1.05 A	2h 00m
1C	2.1 A	1h 00m
2C	4.2 A	30m
3C	6.3 A	20m
5C	10.5 A	12m
8C	16.8 A	7m 30s
10C	21 A	6m

15C

31.5 A

4m

Highlighted row is closest to the rated 38 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
0.5C	1,050 mA	~2h 00m
Standard	2,000 mA	~1h 03m
1C	2,100 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	6.3 Ah	68 Wh
7S	25.2 V	29.4 V	21	6.3 Ah	159 Wh
10S	36 V	42 V	30	6.3 Ah	227 Wh
13S	46.8 V	54.6 V	39	6.3 Ah	295 Wh
14S	50.4 V	58.8 V	42	6.3 Ah	318 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 4,200 mAh · 106 Wh 76 A max	13S4P 48V ebike standard 52 cells · 46.8 V 8,400 mAh · 393 Wh 152 A max	16S4P DIY powerwall 64 cells · 57.6 V 8,400 mAh · 484 Wh 152 A max	4S6P Power tool replacement 24 cells · 14.4 V 12,600 mAh · 181 Wh 228 A max
--	--	---	--

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Efest 18650 2100mAh 38A (this cell)	2,100	38 A	7.56	—	—
AWT 40A 2600mAh	2,600	40 A	9.4	60 g	156
AWT YELLOW 40A 2600mAh	2,600	40 A	9.4	60 g	156
Golisi S26	2,600	25 A	9.4	46 g	203
Xtar XTVTC4	2,200	25 A	7.9	—	—
Efest PURPLE 30A 2100mAh	2,100	30 A	7.6	—	—

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Savors page	cellsaviors.com/cell-database/efest-18650-2100mah-38a
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/efest-38a-2100mah-18...
Full cell database	cellsaviors.com/cell-database