

Illustrative render generated from published specifications

18.23 × 65.02 mm
46 g

Efest 18650

2800mAh 35A



Live page & updates

Efest · released 2015

- 18650
- LMO
- MOOCH-TESTED · 35 A

2,800 mAh CAPACITY	35 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	10.08 Wh ENERGY · 219.13 WH/KG
--	---	---	--

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S #77 of 279 Lowest in databaseHighest Higher discharge than 94% of 18650 cells in our database. Great for high-drain builds.	VOLTAGE OPERATING WINDOW 1.7 V usable Cutoff 2.5 VNominal 3.6 VMax 4.2 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
--	--

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Enough discharge to handle amplifier bursts without voltage sag.
High-drain vaping	Above the 25A Mooch CDR threshold. Suitable for regulated and mechanical mods.
Flashlights	Decent runtime. Works well for most flashlights.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY

Manufacturer	Efest
Model	18650 2800mAh 35A
Format	18650
Chemistry	LMO
Year released	2015
Wrap colour	Purple
Terminal	Flat top
Protection	Unprotected

OPERATING TEMPERATURE

Charging	0°C to 45°C
Discharging	-20°C to 60°C

ENERGY & POWER DENSITY

Energy	10.08 Wh
Specific energy	219.13 Wh/kg
Volumetric density	593.95 Wh/L
Power density (mass)	2,739 W/kg
Power density (volume)	7,424 W/L
Capacity ranking	#77 of 279 18650s

C-RATE CONVERSION · 2,800 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.56 A	5h 00m
0.5C	1.4 A	2h 00m
1C	2.8 A	1h 00m
2C	5.6 A	30m
3C	8.4 A	20m
5C	14 A	12m

PHYSICAL

Diameter	18.23 mm
Length	65.02 mm
Weight	46 g

ELECTRICAL

Rated capacity	2,800 mAh
Nominal voltage	3.6 V
Max charge voltage	4.2 V
Discharge cutoff	2.5 V
Energy	10.08 Wh
Max continuous discharge	35 A (mooch)
Discharge C-rate	12.5C
Standard charge current	2,000 mA
Typical charge time	1.4 h

8C	22.4 A	7m 30s
10C	28 A	6m

Highlighted row is closest to the rated 35 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
0.5C	1,400 mA	~2h 00m
Standard	2,000 mA	~1h 24m
1C	2,800 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	8.4 Ah	91 Wh
7S	25.2 V	29.4 V	21	8.4 Ah	212 Wh
10S	36 V	42 V	30	8.4 Ah	302 Wh
13S	46.8 V	54.6 V	39	8.4 Ah	393 Wh
14S	50.4 V	58.8 V	42	8.4 Ah	423 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 5,600 mAh · 141 Wh 70 A max · ≈0.64 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 11,200 mAh · 524 Wh 140 A max · ≈2.39 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 11,200 mAh · 645 Wh 140 A max · ≈2.94 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 16,800 mAh · 242 Wh 210 A max · ≈1.1 kg cells
---	--	---	--

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Efest 18650 2800mAh 35A (this cell)	2,800	35 A	10.08	46 g	219
AWT 40A 3300mAh	3,300	40 A	11.9	54 g	220
Efest EFEST 35A 2900mAh	2,900	35 A	10.4	—	—
AWT 40A 2600mAh	2,600	40 A	9.4	60 g	156
AWT YELLOW 40A 2600mAh	2,600	40 A	9.4	60 g	156
Golisi S26	2,600	25 A	9.4	46 g	203

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Savors page	cellsaviors.com/cell-database/efest-18650-2800mah-35a
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/efest-35a-2800mah-18...
Full cell database	cellsaviors.com/cell-database