

Illustrative render generated from published specifications

20.35 × 70.3 mm
63 g

Energig 20700
4000mAh 15A



Live page & updates

Energig

- 20700
- NCA
- MOOCH-TESTED · 15 A

4,000 mAh CAPACITY	15 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	14.4 Wh ENERGY · 228.57 WH/KG
--	---	---	---

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 20700S #3 of 12 Lowest in database Highest More capacity than 83% of 20700 cells in our database, but lower discharge than average.	VOLTAGE OPERATING WINDOW 1.7 V usable Cutoff 2.5 V Nominal 3.6 V Max 4.2 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
--	---

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Might work for smaller setups. Check your amp's peak current draw.
High-drain vaping	Usable in regulated mods at moderate wattage. Not recommended for mechanical mods.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY

Manufacturer	Energig
Model	20700 4000mAh 15A
Format	20700
Chemistry	NCA
Wrap colour	Red
Terminal	Flat top
Protection	Unprotected

OPERATING TEMPERATURE

Charging	10°C to 45°C
Discharging	-20°C to 60°C

ENERGY & POWER DENSITY

Energy	14.4 Wh
Specific energy	228.57 Wh/kg
Volumetric density	629.78 Wh/L
Power density (mass)	857 W/kg
Power density (volume)	2,362 W/L
Capacity ranking	#3 of 12 20700s

PHYSICAL

Diameter	20.35 mm
Length	70.3 mm
Weight	63 g

ELECTRICAL

Rated capacity	4,000 mAh
Nominal voltage	3.6 V
Max charge voltage	4.2 V
Discharge cutoff	2.5 V
Energy	14.4 Wh
Max continuous discharge	15 A (mooch)
Discharge C-rate	3.8C
Standard charge current	2,000 mA
Typical charge time	2 h
Standard discharge	800mA

C-RATE CONVERSION · 4,000 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.8 A	5h 00m
0.5C	2 A	2h 00m
1C	4 A	1h 00m
2C	8 A	30m
3C	12 A	20m

Highlighted row is closest to the rated 15 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
0.5C	2,000 mA	~2h 00m
1C	4,000 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	12 Ah	130 Wh
7S	25.2 V	29.4 V	21	12 Ah	302 Wh
10S	36 V	42 V	30	12 Ah	432 Wh
13S	46.8 V	54.6 V	39	12 Ah	562 Wh
14S	50.4 V	58.8 V	42	12 Ah	605 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 8,000 mAh · 202 Wh 30 A max · ≈0.88 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 16,000 mAh · 749 Wh 60 A max · ≈3.28 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 16,000 mAh · 922 Wh 60 A max · ≈4.03 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 24,000 mAh · 346 Wh 90 A max · ≈1.51 kg cells
---	---	--	--

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Energig 20700 4000mAh 15A (this cell)	4,000	15 A	14.4	63 g	229
Keeppower NCR20700B	4,250	15 A	15.3	63 g	243

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.

- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/energig-20700-4000mah-15a
Manufacturer datasheet	https://datasheetspdf.com/pdf/1265185/Panasonic/NCR20700B/1
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-e...
Full cell database	cellsaviors.com/cell-database