

Illustrative render generated from published specifications

GP Batteries

GP1865L180



Live page & updates

GP Batteries

- 18650
- NMC

1,800 mAh CAPACITY	1.8 A RATED CONTINUOUS	3.7 V NOMINAL · 2.8 – 4.2 V	6.66 Wh ENERGY
--	--	---	--------------------------------------

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S

#144 of 169

Lowest in database

Highest

A mid-range 18650 cell. Solid for builds that don't need extreme capacity or discharge.

VOLTAGE OPERATING WINDOW

1.4 V usable

Cutoff 2.8 V

Nominal 3.7 V

Max 4.2 V

Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	Usable for powerwalls but lower capacity means you'll need more cells to hit your target kWh.
Ebike packs	Not enough discharge for ebike use. Voltage sag would be a problem under load.
Car audio	Not enough discharge for car audio amplifiers. You need at least 15-20A continuous for most setups.
High-drain vaping	Below the 25A Moolch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	Lower capacity means shorter runtime. Better cells are available for flashlight use.
Power tools	Not enough discharge or capacity for power tool use.

IDENTITY		ELECTRICAL	
Manufacturer	GP Batteries	Rated capacity	1,800 mAh
Model	GP1865L180	Nominal voltage	3.7 V
Format	18650	Max charge voltage	4.2 V
Chemistry	NMC	Discharge cutoff	2.8 V
Wrap colour	Orange	Energy	6.66 Wh
Insulator	Black	Max continuous discharge	1.8 A (datasheet)
ENERGY & POWER DENSITY		Discharge C-rate	1C
Energy	6.66 Wh	Standard charge current	1,080 mA
Capacity ranking	#144 of 169 18650s	Typical charge time	1.7 h
		Standard discharge	520mA

C-RATE CONVERSION · 1,800 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.36 A	5h 00m
0.5C	0.9 A	2h 00m
1C	1.8 A	1h 00m

Highlighted row is closest to the rated 1.8 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
0.5C	900 mA	~2h 00m
Standard	1,080 mA	~1h 40m
1C	1,800 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	11.1 V	12.6 V	9	5.4 Ah	60 Wh

7S	25.9 V	29.4 V	21	5.4 Ah	140 Wh
10S	37 V	42 V	30	5.4 Ah	200 Wh
13S	48.1 V	54.6 V	39	5.4 Ah	260 Wh
14S	51.8 V	58.8 V	42	5.4 Ah	280 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.9 V 3,600 mAh · 93 Wh 4 A max	13S4P 48V ebike standard 52 cells · 48.1 V 7,200 mAh · 346 Wh 7 A max	16S4P DIY powerwall 64 cells · 59.2 V 7,200 mAh · 426 Wh 7 A max	4S6P Power tool replacement 24 cells · 14.8 V 10,800 mAh · 160 Wh 11 A max
--	--	---	---

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
GP Batteries GP1865L180 (this cell)	1,800	1.8 A	6.66	—	—
Moli Energy ICR-18650J	2,300	5 A	8.5	48 g	177
BAK 18650C4	2,200	2 A	8.1	—	—
BFN 18650-2200	2,200	25 A	8.1	—	—
Great Power ICR18650 2.2Ah-AT	2,200	4.4 A	8.1	45 g	181
LG LGAAS41865	2,200	45 A	8.1	44.5 g	183

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.8V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Savors page

cellsaviors.com/cell-database/gp-batteries-gp1865l180

Full cell database

cellsaviors.com/cell-database