

Illustrative render generated from published specifications

18.23 × 65.12 mm
44.7 g

Hohm Tech LIFE4

Hohm Tech · released 2020

18650 NMC

MOOCH-TESTED · 22 A



Live page & updates

3,015 mAh CAPACITY	22 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	10.85 Wh ENERGY · 242.73 WH/KG
--	---	---	--

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S #35 of 279 Lowest in databaseHighest Top tier for both capacity and discharge. One of the best all-around 18650 cells.	VOLTAGE OPERATING WINDOW 1.7 V usable Cutoff 2.5 VNominal 3.6 VMax 4.2 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
--	--

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Enough discharge to handle amplifier bursts without voltage sag.
High-drain vaping	Usable in regulated mods at moderate wattage. Not recommended for mechanical mods.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY		PHYSICAL	
Manufacturer	Hohm Tech	Diameter	18.23 mm
Model	LIFE4	Length	65.12 mm
Format	18650	Weight	44.7 g
Chemistry	NMC	ELECTRICAL	
Year released	2020		
Wrap colour	■ Black		
Terminal	Flat top		
Protection	Unprotected		
ENERGY & POWER DENSITY		Rated capacity	3,015 mAh
Energy	10.85 Wh	Nominal voltage	3.6 V
Specific energy	242.73 Wh/kg	Max charge voltage	4.2 V
Volumetric density	638.34 Wh/L	Discharge cutoff	2.5 V
Power density (mass)	1,772 W/kg	Energy	10.85 Wh
Power density (volume)	4,660 W/L	Internal resistance	16.8 mΩ
Capacity ranking	#35 of 279 18650s	Max continuous discharge	22 A (mooch)
		Discharge C-rate	7.3C
		Standard charge current	4,430 mA
		Typical charge time	0.7 h
		Cycle life	500 cycles

C-RATE CONVERSION · 3,015 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.6 A	5h 00m
0.5C	1.51 A	2h 00m
1C	3.02 A	1h 00m
2C	6.03 A	30m
3C	9.05 A	20m
5C	15.08 A	12m

Highlighted row is closest to the rated 22 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
0.5C	1,508 mA	~2h 00m

1C	3,015 mA	~1h 00m
Standard	4,430 mA	~0h 41m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	9 Ah	98 Wh
7S	25.2 V	29.4 V	21	9 Ah	228 Wh
10S	36 V	42 V	30	9 Ah	326 Wh
13S	46.8 V	54.6 V	39	9 Ah	423 Wh
14S	50.4 V	58.8 V	42	9 Ah	456 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 6,030 mAh · 152 Wh 44 A max · ≈0.63 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 12,060 mAh · 564 Wh 88 A max · ≈2.32 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 12,060 mAh · 695 Wh 88 A max · ≈2.86 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 18,090 mAh · 260 Wh 132 A max · ≈1.07 kg cells
---	---	--	---

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Hohm Tech LIFE4 (this cell)	3,015	22 A	10.85	44.7 g	243
LG LGEBMJ11865	3,500	10 A	12.7	49 g	260
LG LGDBMJ11865	3,500	10 A	12.7	49 g	259
AWT AWT 35A 3500mAh	3,500	35 A	12.6	—	—
Epoch PROTECTED	3,500	8 A	12.6	49.1 g	257
EVE INR18650-35V	3,500	10 A	12.6	47 g	268

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/hohm-tech-life4
Manufacturer datasheet	https://hohmtech.com/download-center/
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-h...
Full cell database	cellsaviors.com/cell-database