

Illustrative render generated from published specifications

20.3 × 65 mm
58 g

LG HG6

LG · released 2016

20650 NMC

MOOCH-TESTED · 30 A



Live page & updates

3,000 mAh CAPACITY	30 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2 – 4.2 V	10.8 Wh ENERGY · 186.21 WH/KG
--	---	---	---

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 20650S #2 of 3 Lowest in databaseHighest Higher discharge than 100% of 20650 cells in our database. Great for high-drain builds.	VOLTAGE OPERATING WINDOW 2.2 V usable Cutoff 2 VNominal 3.6 VMax 4.2 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
--	---

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Enough discharge to handle amplifier bursts without voltage sag.
High-drain vaping	Above the 25A Moolch CDR threshold. Suitable for regulated and mechanical mods.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY

Manufacturer	LG
Model	HG6
Format	20650
Chemistry	NMC
Year released	2016
Wrap colour	■ Blue
Terminal	Flat top
Protection	Unprotected

OPERATING TEMPERATURE

Charging	0°C to 50°C
Discharging	-20°C to 75°C

ENERGY & POWER DENSITY

Energy	10.8 Wh
Specific energy	186.21 Wh/kg
Volumetric density	513.37 Wh/L
Power density (mass)	1,862 W/kg
Power density (volume)	5,134 W/L
Capacity ranking	#2 of 3 20650s

PHYSICAL

Diameter	20.3 mm
Length	65 mm
Weight	58 g

ELECTRICAL

Rated capacity	3,000 mAh
Nominal voltage	3.6 V
Max charge voltage	4.2 V
Discharge cutoff	2 V
Energy	10.8 Wh
Max continuous discharge	30 A (mooch)
Discharge C-rate	10C
Standard charge current	1,500 mA
Typical charge time	2 h
Standard discharge	600mA

C-RATE CONVERSION · 3,000 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.6 A	5h 00m
0.5C	1.5 A	2h 00m
1C	3 A	1h 00m
2C	6 A	30m
3C	9 A	20m
5C	15 A	12m

8C

24 A

7m 30s

10C

30 A

6m

Highlighted row is closest to the rated 30 A continuous discharge.

CHARGING

Rate	Current	Estimated Time to Full
0.5C	1,500 mA	~2h 00m
1C	3,000 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

Series	Nominal	Fully Charged	Cells at 3P	Capacity	Energy
3S	10.8 V	12.6 V	9	9 Ah	97 Wh
7S	25.2 V	29.4 V	21	9 Ah	227 Wh
10S	36 V	42 V	30	9 Ah	324 Wh
13S	46.8 V	54.6 V	39	9 Ah	421 Wh
14S	50.4 V	58.8 V	42	9 Ah	454 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 6,000 mAh · 151 Wh 60 A max · ≈0.81 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 12,000 mAh · 562 Wh 120 A max · ≈3.02 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 12,000 mAh · 691 Wh 120 A max · ≈3.71 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 18,000 mAh · 259 Wh 180 A max · ≈1.39 kg cells
---	--	---	---

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
LG HG6 (this cell)	3,000	30 A	10.8	58 g	186
FST 20650-3350mAh	3,350	6.7 A	12.1	—	—
Vapcell PURPLE 30A 3000mAh	3,000	30 A	10.8	56 g	193

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/lg-hg6
Manufacturer datasheet	https://files.batteryjunction.com/frontend/files/lg/datasheet/...
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-l...
Full cell database	cellsaviors.com/cell-database