

Illustrative render generated from published specifications

18.29 × 65.05 mm
49 g

LG LGABE11865

LG · also sold as ICR18650E1 · released 2012



Live page & updates

18650

NMC

MOOCH-TESTED · 9 A

3,200 mAh CAPACITY	9 A MOOCH CONTINUOUS	3.75 V NOMINAL · 2.8 – 4.35 V	12 Wh ENERGY · 244.9 WH/KG
--	--	---	--

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S #7 of 169 Lowest in databaseHighest More capacity than 96% of 18650 cells in our database. One of the higher-capacity options.	VOLTAGE OPERATING WINDOW 1.55 V usable Cutoff 2.8 VNominal 3.75 VMax 4.35 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
---	--

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Marginal. Check your motor's peak draw first. You might get voltage sag under load.
Car audio	Not enough discharge for car audio amplifiers. You need at least 15-20A continuous for most setups.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	Not enough discharge or capacity for power tool use.

IDENTITY

Manufacturer	LG
Model	LGABE11865
Also sold as	ICR18650E1
Format	18650
Chemistry	NMC
Year released	2012
Wrap colour	Teal
Insulator	White
Terminal	Flat top
Protection	Unprotected

OPERATING TEMPERATURE

Charging	0°C to 45°C
Discharging	-20°C to 50°C

ENERGY & POWER DENSITY

Energy	12 Wh
Specific energy	244.9 Wh/kg
Volumetric density	702.13 Wh/L
Power density (mass)	689 W/kg
Power density (volume)	1,975 W/L
Capacity ranking	#7 of 169 18650s

C-RATE CONVERSION · 3,200 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.64 A	5h 00m
0.5C	1.6 A	2h 00m
1C	3.2 A	1h 00m
2C	6.4 A	30m

Highlighted row is closest to the rated 9 A continuous discharge.

PHYSICAL

Diameter	18.29 mm
Length	65.05 mm
Weight	49 g

ELECTRICAL

Rated capacity	3,200 mAh
Nominal voltage	3.75 V
Max charge voltage	4.35 V
Discharge cutoff	2.8 V
Energy	12 Wh
Internal resistance	70 mΩ
Max continuous discharge	9 A (mooch)
Discharge C-rate	2.8C
Standard charge current	1,550 mA
Typical charge time	2.1 h
Standard discharge	620mA

CHARGING

Rate	Current	Estimated Time to Full
0.5C	1,600 mA	~2h 00m
1C	3,200 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

Series	Nominal	Fully Charged	Cells at 3P	Capacity	Energy
3S	11.3 V	13 V	9	9.6 Ah	108 Wh
7S	26.3 V	30.4 V	21	9.6 Ah	252 Wh
10S	37.5 V	43.5 V	30	9.6 Ah	360 Wh
13S	48.8 V	56.6 V	39	9.6 Ah	468 Wh
14S	52.5 V	60.9 V	42	9.6 Ah	504 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 26.3 V 6,400 mAh · 168 Wh 18 A max · ≈0.69 kg cells	13S4P 48V ebike standard 52 cells · 48.8 V 12,800 mAh · 624 Wh 36 A max · ≈2.55 kg cells	16S4P DIY powerwall 64 cells · 60 V 12,800 mAh · 768 Wh 36 A max · ≈3.14 kg cells	4S6P Power tool replacement 24 cells · 15 V 19,200 mAh · 288 Wh 54 A max · ≈1.18 kg cells
--	--	---	---

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
LG LGABE11865 (this cell)	3,200	9 A	12	49 g	245
LG LGEBMJ11865	3,500	10 A	12.7	—	—
LG LGDBMJ11865	3,500	10 A	12.7	49 g	259
LG LGABF1L1865	3,350	4.9 A	12.2	49 g	248
LG LGGBF1L1865	3,350	4.9 A	12.2	—	—
Panasonic NCR18650B	3,350	4 A	12.1	47.5 g	254

HANDLING & SAFETY

- Never charge above 4.35V or discharge below 2.8V.
- Store cells at around 3.6–3.8V (roughly 40–60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Savors page	cellsaviors.com/cell-database/lg-lgabe11865
Manufacturer datasheet	https://www.dnkpowers.com/wp-content/uploads/2022/11/LG-ICR1865...
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-s...
Full cell database	cellsaviors.com/cell-database