

Illustrative render generated from published specifications

18.29 × 65 mm
47 g

LG LGDC118650

LG · also sold as ICR18650C1

18650 NMC



Live page & updates

2,800 mAh CAPACITY	4.1 A RATED CONTINUOUS	3.75 V NOMINAL · 3 – 4.35 V	10.5 Wh ENERGY · 223.4 WH/KG
--	--	---	--

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S #28 of 169 Lowest in databaseHighest More capacity than 84% of 18650 cells in our database, but lower discharge than average.	VOLTAGE OPERATING WINDOW 1.35 V usable Cutoff 3 VNominal 3.75 VMax 4.35 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
---	---

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Not enough discharge for ebike use. Voltage sag would be a problem under load.
Car audio	Not enough discharge for car audio amplifiers. You need at least 15-20A continuous for most setups.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	Decent runtime. Works well for most flashlights.
Power tools	Not enough discharge or capacity for power tool use.

IDENTITY

Manufacturer	LG
Model	LGDC118650
Also sold as	ICR18650C1
Format	18650
Chemistry	NMC
Wrap colour	Brown
Insulator	White
Terminal	Flat top
Protection	Unprotected

OPERATING TEMPERATURE

Charging	0°C to 45°C
Discharging	-20°C to 60°C

ENERGY & POWER DENSITY

Energy	10.5 Wh
Specific energy	223.4 Wh/kg
Volumetric density	614.84 Wh/L
Power density (mass)	327 W/kg
Power density (volume)	900 W/L
Capacity ranking	#28 of 169 18650s

C-RATE CONVERSION · 2,800 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.56 A	5h 00m
0.5C	1.4 A	2h 00m
1C	2.8 A	1h 00m

Highlighted row is closest to the rated 4.1 A continuous discharge.

PHYSICAL

Diameter	18.29 mm
Length	65 mm
Weight	47 g

ELECTRICAL

Rated capacity	2,800 mAh
Nominal voltage	3.75 V
Max charge voltage	4.35 V
Discharge cutoff	3 V
Energy	10.5 Wh
Internal resistance	70 mΩ
Max continuous discharge	4.1 A (datasheet)
Discharge C-rate	1.5C
Standard charge current	1,350 mA
Typical charge time	2.1 h
Standard discharge	540ma
Cycle life	300 cycles

CHARGING

Rate	Current	Estimated Time to Full
0.5C	1,400 mA	~2h 00m
1C	2,800 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

Series	Nominal	Fully Charged	Cells at 3P	Capacity	Energy
3S	11.3 V	13 V	9	8.4 Ah	95 Wh
7S	26.3 V	30.4 V	21	8.4 Ah	221 Wh
10S	37.5 V	43.5 V	30	8.4 Ah	315 Wh
13S	48.8 V	56.6 V	39	8.4 Ah	410 Wh
14S	52.5 V	60.9 V	42	8.4 Ah	441 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 26.3 V 5,600 mAh · 147 Wh 8 A max · ≈0.66 kg cells	13S4P 48V ebike standard 52 cells · 48.8 V 11,200 mAh · 546 Wh 16 A max · ≈2.44 kg cells	16S4P DIY powerwall 64 cells · 60 V 11,200 mAh · 672 Wh 16 A max · ≈3.01 kg cells	4S6P Power tool replacement 24 cells · 15 V 16,800 mAh · 252 Wh 25 A max · ≈1.13 kg cells
---	--	---	---

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
LG LGDC118650 (this cell)	2,800	4.1 A	10.5	47 g	223
LG LGABE11865	3,200	9 A	12	49 g	245
LG LGEBE11865	3,200	4.9 A	12	—	—
Samsung ICR18650-32A	3,200	6.4 A	12	50 g	240
Sanyo NCR18650GA	3,300	10 A	11.9	48 g	248
EVE EVE-INR18650/33V	3,200	10 A	11.5	—	—

HANDLING & SAFETY

- Never charge above 4.35V or discharge below 3V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Savors page	cellsaviors.com/cell-database/lg-lgdc118650
Full cell database	cellsaviors.com/cell-database