

Illustrative render generated from published specifications

LG LGEBMF21865



Live page & updates

LG

18650

NMC

2,200 mAh CAPACITY	10 A RATED CONTINUOUS	3.6 V NOMINAL · 2.8 – 4.2 V	7.92 Wh ENERGY
--	---	---	--------------------------------------

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S

#87 of 169

Lowest in database

Highest

Higher discharge than 80% of 18650 cells in our database.

Great for high-drain builds.

VOLTAGE OPERATING WINDOW

1.4 V usable

Cutoff 2.8 V

Nominal 3.6 V

Max 4.2 V

Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	Usable for powerwalls but lower capacity means you'll need more cells to hit your target kWh.
Ebike packs	Marginal. Check your motor's peak draw first. You might get voltage sag under load.
Car audio	Might work for smaller setups. Check your amp's peak current draw.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	Lower capacity means shorter runtime. Better cells are available for flashlight use.
Power tools	May work for lighter-duty tools. Check your tool's current requirements.

IDENTITY		ELECTRICAL	
Manufacturer	LG	Rated capacity	2,200 mAh
Model	LGEBMF21865	Nominal voltage	3.6 V
Format	18650	Max charge voltage	4.2 V
Chemistry	NMC	Discharge cutoff	2.8 V
Wrap colour	Purple (Dark)	Energy	7.92 Wh
Insulator	White	Internal resistance	60 mΩ
ENERGY & POWER DENSITY		Max continuous discharge	10 A (datasheet)
Energy	7.92 Wh	Discharge C-rate	4.5C
Capacity ranking	#87 of 169 18650s	Standard charge current	1,050 mA
		Typical charge time	2.1 h
		Standard discharge	420mA

C-RATE CONVERSION · 2,200 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.44 A	5h 00m
0.5C	1.1 A	2h 00m
1C	2.2 A	1h 00m
2C	4.4 A	30m
3C	6.6 A	20m

Highlighted row is closest to the rated 10 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
0.5C	1,100 mA	~2h 00m
1C	2,200 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	6.6 Ah	71 Wh
7S	25.2 V	29.4 V	21	6.6 Ah	166 Wh
10S	36 V	42 V	30	6.6 Ah	238 Wh
13S	46.8 V	54.6 V	39	6.6 Ah	309 Wh
14S	50.4 V	58.8 V	42	6.6 Ah	333 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 4,400 mAh · 111 Wh 20 A max	13S4P 48V ebike standard 52 cells · 46.8 V 8,800 mAh · 412 Wh 40 A max	16S4P DIY powerwall 64 cells · 57.6 V 8,800 mAh · 507 Wh 40 A max	4S6P Power tool replacement 24 cells · 14.4 V 13,200 mAh · 190 Wh 60 A max
--	---	--	---

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
LG LGEBMF21865 (this cell)	2,200	10 A	7.92	—	—
Panasonic NCR18650D	2,700	5.1 A	10	—	—
Sanyo UR18650ZT	2,650	5.3 A	9.8	46 g	213
LG LGDB118650	2,600	—	9.8	—	—
LG LGDBB11865	2,600	—	9.8	—	—
Sanyo UR18650ZTA	2,620	5.8 A	9.7	48 g	202

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.8V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/lg-lgebmf21865
Full cell database	cellsaviors.com/cell-database