

Illustrative render generated from published specifications

21.7 × 70.9 mm

Lishen LR2170SK

Lishen

21700

NMC

MOOCH-TESTED · 16 A



Live page & updates

5,800 mAh CAPACITY	16 A MOOCH CONTINUOUS	3.6 v NOMINAL · 2.75 – 4.2 V	20.88 Wh ENERGY
--	---	--	---------------------------------------

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 21700S

#10 of 72

Lowest in databaseHighest

More capacity than 88% of 21700 cells in our database, but lower discharge than average.

VOLTAGE OPERATING WINDOW

1.45 V usable

Cutoff 2.75 VNominal 3.6 VMax 4.2 V

Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Might work for smaller setups. Check your amp's peak current draw.
High-drain vaping	Usable in regulated mods at moderate wattage. Not recommended for mechanical mods.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY

Manufacturer	Lishen
Model	LR2170SK
Format	21700
Chemistry	NMC
Terminal	Flat top
Protection	Unprotected

OPERATING TEMPERATURE

Charging	0°C to 55°C
Discharging	-20°C to 60°C

ENERGY & POWER DENSITY

Energy	20.88 Wh
Volumetric density	796.3 Wh/L
Power density (volume)	2,197 W/L
Capacity ranking	#10 of 72 21700s

PHYSICAL

Diameter	21.7 mm
Length	70.9 mm

ELECTRICAL

Rated capacity	5,800 mAh
Nominal voltage	3.6 V
Max charge voltage	4.2 V
Discharge cutoff	2.75 V
Energy	20.88 Wh
Max continuous discharge	16 A (mooch)
Discharge C-rate	2.8C
Standard charge current	1,160 mA
Typical charge time	5 h
Standard discharge	1160mA
Cycle life	500 cycles

C-RATE CONVERSION · 5,800 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	1.16 A	5h 00m
0.5C	2.9 A	2h 00m
1C	5.8 A	1h 00m
2C	11.6 A	30m

Highlighted row is closest to the rated 16 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
Standard	1,160 mA	~5h 00m
0.5C	2,900 mA	~2h 00m
1C	5,800 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	17.4 Ah	188 Wh
7S	25.2 V	29.4 V	21	17.4 Ah	438 Wh
10S	36 V	42 V	30	17.4 Ah	626 Wh
13S	46.8 V	54.6 V	39	17.4 Ah	814 Wh
14S	50.4 V	58.8 V	42	17.4 Ah	877 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 11,600 mAh · 292 Wh 32 A max	13S4P 48V ebike standard 52 cells · 46.8 V 23,200 mAh · 1,086 Wh 64 A max	16S4P DIY powerwall 64 cells · 57.6 V 23,200 mAh · 1,336 Wh 64 A max	4S6P Power tool replacement 24 cells · 14.4 V 34,800 mAh · 501 Wh 96 A max
---	--	---	---

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Lishen LR2170SK (this cell)	5,800	16 A	20.88	—	—
Vapcell F63	6,250	12 A	22.5	—	—
Linkdata 60P	6,000	60 A	21.6	68 g	318
Vapcell F60	6,000	12 A	21.6	74 g	292
Reliance RH60	5,850	20 A	21.1	71 g	297
Reliance RS60	5,850	50 A	21.1	71.5 g	295

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.75V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.

- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/lishen-lr2170sk
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-l...
Full cell database	cellsaviors.com/cell-database