

Illustrative render generated from published specifications

18.2 × 36.4 mm
22 g

Nitecore 18350
700mAh 7A



Live page & updates

Nitecore

- 18350
- LMO
- MOOCH-TESTED · 7 A

700 mAh CAPACITY	7 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.75 – 4.2 V	2.52 Wh ENERGY · 114.55 WH/KG
--	--	--	---

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18350S #9 of 10 Lowest in databaseHighest A mid-range 18350 cell. Solid for builds that don't need extreme capacity or discharge.	VOLTAGE OPERATING WINDOW 1.45 V usable Cutoff 2.75 VNominal 3.6 VMax 4.2 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
---	---

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	Too low capacity for practical powerwall use. You'd need too many cells.
Ebike packs	Not enough discharge for ebike use. Voltage sag would be a problem under load.
Car audio	Not enough discharge for car audio amplifiers. You need at least 15-20A continuous for most setups.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	Lower capacity means shorter runtime. Better cells are available for flashlight use.
Power tools	Not enough discharge or capacity for power tool use.

IDENTITY

Manufacturer	Nitecore
Model	18350 700mAh 7A
Format	18350
Chemistry	LMO
Wrap colour	■ Black
Terminal	Button top
Protection	Unprotected

ENERGY & POWER DENSITY

Energy	2.52 Wh
Specific energy	114.55 Wh/kg
Volumetric density	266.11 Wh/L
Power density (mass)	1,145 W/kg
Power density (volume)	2,661 W/L
Capacity ranking	#9 of 10 18350s

PHYSICAL

Diameter	18.2 mm
Length	36.4 mm
Weight	22 g

ELECTRICAL

Rated capacity	700 mAh
Nominal voltage	3.6 V
Max charge voltage	4.2 V
Discharge cutoff	2.75 V
Energy	2.52 Wh
Max continuous discharge	7 A (mooch)
Discharge C-rate	10C
Cycle life	500 cycles

C-RATE CONVERSION · 700 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.14 A	5h 00m
0.5C	0.35 A	2h 00m
1C	0.7 A	1h 00m
2C	1.4 A	30m
3C	2.1 A	20m
5C	3.5 A	12m
8C	5.6 A	7m 30s
10C	7 A	6m

Highlighted row is closest to the rated 7 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
------	---------	------------------------

0.5C	350 mA	~2h 00m
1C	700 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	2.1 Ah	23 Wh
7S	25.2 V	29.4 V	21	2.1 Ah	53 Wh
10S	36 V	42 V	30	2.1 Ah	76 Wh
13S	46.8 V	54.6 V	39	2.1 Ah	98 Wh
14S	50.4 V	58.8 V	42	2.1 Ah	106 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 1,400 mAh · 35 Wh 14 A max · ≈0.31 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 2,800 mAh · 131 Wh 28 A max · ≈1.14 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 2,800 mAh · 161 Wh 28 A max · ≈1.41 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 4,200 mAh · 60 Wh 42 A max · ≈0.53 kg cells
--	--	---	--

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Nitecore 18350 700mAh 7A (this cell)	700	7 A	2.52	22 g	115
Epoch 18350	1,100	9 A	4	26 g	152
AWT 18350	850	10 A	3.1	22.1 g	138
AW 18350	800	12 A	2.9	—	—
Efest IMR18350	700	10 A	2.5	28 g	90

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.75V.

- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/nitecore-18350-700mah-7a
Manufacturer datasheet	https://flashlight.nitecore.com/product/imr18350
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-n...
Full cell database	cellsaviors.com/cell-database