

Illustrative render generated from published specifications

18.4 × 65 mm

Samsung
ICR18650-20B



Live page & updates

Samsung

- 18650
- NMC

2,000 mAh CAPACITY	4 A RATED CONTINUOUS	3.7 V NOMINAL · 2.8 – 4.2 V	7.4 Wh ENERGY
--	--	---	-------------------------------------

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S #127 of 169 Lowest in database Highest A mid-range 18650 cell. Solid for builds that don't need extreme capacity or discharge.	VOLTAGE OPERATING WINDOW 1.4 V usable Cutoff 2.8 V Nominal 3.7 V Max 4.2 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
--	---

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	Usable for powerwalls but lower capacity means you'll need more cells to hit your target kWh.
Ebike packs	Not enough discharge for ebike use. Voltage sag would be a problem under load.
Car audio	Not enough discharge for car audio amplifiers. You need at least 15-20A continuous for most setups.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	Lower capacity means shorter runtime. Better cells are available for flashlight use.
Power tools	Not enough discharge or capacity for power tool use.

IDENTITY		PHYSICAL	
Manufacturer	Samsung	Diameter	18.4 mm
Model	ICR18650-20B	Length	65 mm
Format	18650	ELECTRICAL	
Chemistry	NMC		
Wrap colour	☒ Blue (Light)	Rated capacity	2,000 mAh
Insulator	☐ White	Nominal voltage	3.7 V
Terminal	Flat top	Max charge voltage	4.2 V
Protection	Unprotected	Discharge cutoff	2.8 V
OPERATING TEMPERATURE		Energy	7.4 Wh
		Max continuous discharge	4 A (datasheet)
		Discharge C-rate	2C
		Standard charge current	1,000 mA
ENERGY & POWER DENSITY		Typical charge time	2 h
		Standard discharge	400mA
		Cycle life	1,000 cycles
Energy	7.4 Wh		
Volumetric density	428.15 Wh/L		
Power density (volume)	856 W/L		
Capacity ranking	#127 of 169 18650s		

C-RATE CONVERSION · 2,000 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.4 A	5h 00m
0.5C	1 A	2h 00m
1C	2 A	1h 00m
2C	4 A	30m

Highlighted row is closest to the rated 4 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
0.5C	1,000 mA	~2h 00m

1C

2,000 mA

~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	11.1 V	12.6 V	9	6 Ah	67 Wh
7S	25.9 V	29.4 V	21	6 Ah	155 Wh
10S	37 V	42 V	30	6 Ah	222 Wh
13S	48.1 V	54.6 V	39	6 Ah	289 Wh
14S	51.8 V	58.8 V	42	6 Ah	311 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.9 V 4,000 mAh · 104 Wh 8 A max	13S4P 48V ebike standard 52 cells · 48.1 V 8,000 mAh · 385 Wh 16 A max	16S4P DIY powerwall 64 cells · 59.2 V 8,000 mAh · 474 Wh 16 A max	4S6P Power tool replacement 24 cells · 14.8 V 12,000 mAh · 178 Wh 24 A max
---	---	--	---

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Samsung ICR18650-20B (this cell)	2,000	4 A	7.4	—	—
LG LGDBHE21865	2,500	20 A	9.3	48 g	193
Sanyo UR18650F	2,500	5 A	9.3	47 g	197
Sanyo UR18650FM	2,500	5 A	9.3	47 g	197
LG LGCP218650	2,500	—	9	—	—
LG LGDBHE41865	2,500	20 A	9	47 g	191

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.8V.

- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/samsung-icr18650-20b
Manufacturer datasheet	http://www.houseofbatteries.com/documents/ICR18650-20.pdf
Full cell database	cellsaviors.com/cell-database