

Illustrative render generated from published specifications

18.55 × 65.25 mm
48 g

Samsung
INR18650-35E5



Live page & updates

Samsung · released 2015

18650

NMC

MOOCH-TESTED · 8 A

3,350 mAh CAPACITY	8 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.65 – 4.2 V	12.06 Wh ENERGY · 251.25 WH/KG
--	--	--	--

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S

#14 of 279

Lowest in database

Highest

More capacity than 95% of 18650 cells in our database, but lower discharge than average.

VOLTAGE OPERATING WINDOW

1.55 V usable

Cutoff 2.65 V

Nominal 3.6 V

Max 4.2 V

Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Marginal. Check your motor's peak draw first. You might get voltage sag under load.
Car audio	Not enough discharge for car audio amplifiers. You need at least 15-20A continuous for most setups.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	Not enough discharge or capacity for power tool use.

IDENTITY

Manufacturer	Samsung
Model	INR18650-35E5
Format	18650
Chemistry	NMC
Year released	2015
Wrap colour	Pink
Terminal	Flat top
Protection	Unprotected

OPERATING TEMPERATURE

Charging	0°C to 45°C
Discharging	-10°C to 60°C

ENERGY & POWER DENSITY

Energy	12.06 Wh
Specific energy	251.25 Wh/kg
Volumetric density	683.89 Wh/L
Power density (mass)	600 W/kg
Power density (volume)	1,633 W/L
Capacity ranking	#14 of 279 18650s

C-RATE CONVERSION · 3,350 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.67 A	5h 00m
0.5C	1.68 A	2h 00m
1C	3.35 A	1h 00m
2C	6.7 A	30m

Highlighted row is closest to the rated 8 A continuous discharge.

PHYSICAL

Diameter	18.55 mm
Length	65.25 mm
Weight	48 g

ELECTRICAL

Rated capacity	3,350 mAh
Nominal voltage	3.6 V
Max charge voltage	4.2 V
Discharge cutoff	2.65 V
Energy	12.06 Wh
Internal resistance	35 mΩ
Max continuous discharge	8 A (mooch)
Discharge C-rate	2.4C
Standard charge current	1,700 mA
Typical charge time	2 h
Standard discharge	680mA
Cycle life	500 cycles

CHARGING

Rate	Current	Estimated Time to Full
0.5C	1,675 mA	~2h 00m
1C	3,350 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

Series	Nominal	Fully Charged	Cells at 3P	Capacity	Energy
3S	10.8 V	12.6 V	9	10.1 Ah	109 Wh
7S	25.2 V	29.4 V	21	10.1 Ah	253 Wh
10S	36 V	42 V	30	10.1 Ah	362 Wh
13S	46.8 V	54.6 V	39	10.1 Ah	470 Wh
14S	50.4 V	58.8 V	42	10.1 Ah	507 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 6,700 mAh · 169 Wh 16 A max · ≈0.67 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 13,400 mAh · 627 Wh 32 A max · ≈2.5 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 13,400 mAh · 772 Wh 32 A max · ≈3.07 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 20,100 mAh · 289 Wh 48 A max · ≈1.15 kg cells
--	---	---	---

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Samsung INR18650-35E5 (this cell)	3,350	8 A	12.06	48 g	251
Vapcell F38	3,800	10 A	13.7	48 g	285
Vapcell N36	3,650	8 A	13.1	48 g	274
LG LGEBMJ11865	3,500	10 A	12.7	49 g	260
LG LGDBMJ11865	3,500	10 A	12.7	49 g	259
AWT AWT 35A 3500mAh	3,500	35 A	12.6	—	—

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.65V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/samsung-inr18650-35e5
Manufacturer datasheet	https://www.orbtronic.com/content/samsung-35e-datasheet-inr186...
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-s...
Full cell database	cellsaviors.com/cell-database