



Sony US18650VT3

Sony · released 2011

18650

NCA

18.35 × 65.1 mm

45.1 g



Live page & updates

1,500 mAh CAPACITY	20 A RATED CONTINUOUS	3.6 v NOMINAL · 2.5 – 4.2 V	5.4 Wh ENERGY · 119.73 WH/KG
--	---	---	--

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells.

CAPACITY AMONG 18650S

#251 of 279

Lowest in database

Highest

Higher discharge than 77% of 18650 cells in our database. Great for high-drain builds.

VOLTAGE OPERATING WINDOW

1.7 V usable

Cutoff 2.5 V

Nominal 3.6 V

Max 4.2 V

Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	Usable for powerwalls but lower capacity means you'll need more cells to hit your target kWh.
Ebike packs	Not enough discharge for ebike use. Voltage sag would be a problem under load.
Car audio	Enough discharge to handle amplifier bursts without voltage sag.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	Lower capacity means shorter runtime. Better cells are available for flashlight use.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY		PHYSICAL	
Manufacturer	Sony	Diameter	18.35 mm
Model	US18650VT3	Length	65.1 mm
Format	18650	Weight	45.1 g
Chemistry	NCA	ELECTRICAL	
Year released	2011		
Wrap colour	Green	Rated capacity	1,500 mAh
Insulator	Black	Nominal voltage	3.6 V
Terminal	Flat top	Max charge voltage	4.2 V
Protection	Unprotected	Discharge cutoff	2.5 V
ENERGY & POWER DENSITY		Energy	5.4 Wh
		Internal resistance	20 mΩ
Energy	5.4 Wh	Max continuous discharge	20 A (datasheet)
Specific energy	119.73 Wh/kg	Discharge C-rate	13.3C
Volumetric density	313.65 Wh/L	Standard charge current	1,500 mA
Power density (mass)	1,596 W/kg	Typical charge time	1 h
Power density (volume)	4,182 W/L	Standard discharge	1500mA
Capacity ranking	#251 of 279 18650s		

C-RATE CONVERSION · 1,500 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.3 A	5h 00m
0.5C	0.75 A	2h 00m
1C	1.5 A	1h 00m
2C	3 A	30m
3C	4.5 A	20m
5C	7.5 A	12m
8C	12 A	7m 30s
10C	15 A	6m

Highlighted row is closest to the rated 20 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
0.5C	750 mA	~2h 00m
1C	1,500 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	4.5 Ah	49 Wh
7S	25.2 V	29.4 V	21	4.5 Ah	113 Wh
10S	36 V	42 V	30	4.5 Ah	162 Wh
13S	46.8 V	54.6 V	39	4.5 Ah	211 Wh
14S	50.4 V	58.8 V	42	4.5 Ah	227 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 3,000 mAh · 76 Wh 40 A max · ≈0.63 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 6,000 mAh · 281 Wh 80 A max · ≈2.35 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 6,000 mAh · 346 Wh 80 A max · ≈2.89 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 9,000 mAh · 130 Wh 120 A max · ≈1.08 kg cells
--	--	---	--

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Sony US18650VT3 (this cell)	1,500	20 A	5.4	45.1 g	120
Toshiba LGR18650S	1,350	—	4.9	45 g	108
Sony US18650S	1,300	3.5 A	4.7	43 g	109

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.

- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/sony-us18650vt3
Manufacturer datasheet	https://www.avacom.cz/Datasheety/Sony/US18650VTC3.pdf
Full cell database	cellsaviors.com/cell-database