

Illustrative render generated from published specifications

26.1 × 65.5 mm
95 g

Vapcell 26650
4200mAh 32A



Live page & updates

Vapcell

26650

NMC

MOOCH-TESTED · 32 A

4,200 mAh CAPACITY	32 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	15.12 Wh ENERGY · 159.16 WH/KG
--	---	---	--

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 26650S

#9 of 15

Lowest in database

Highest

A mid-range 26650 cell. Solid for builds that don't need extreme capacity or discharge.

VOLTAGE OPERATING WINDOW

1.7 V usable

Cutoff 2.5 V

Nominal 3.6 V

Max 4.2 V

Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Enough discharge to handle amplifier bursts without voltage sag.
High-drain vaping	Above the 25A Mooch CDR threshold. Suitable for regulated and mechanical mods.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY		PHYSICAL	
Manufacturer	Vapcell	Diameter	26.1 mm
Model	26650 4200mAh 32A	Length	65.5 mm
Format	26650	Weight	95 g
Chemistry	NMC	ELECTRICAL	
Wrap colour	Purple		
Insulator	White		
Terminal	Flat top		
Protection	Unprotected		
ENERGY & POWER DENSITY		Rated capacity	4,200 mAh
Energy	15.12 Wh	Nominal voltage	3.6 V
Specific energy	159.16 Wh/kg	Max charge voltage	4.2 V
Volumetric density	431.46 Wh/L	Discharge cutoff	2.5 V
Power density (mass)	1,213 W/kg	Energy	15.12 Wh
Power density (volume)	3,287 W/L	Internal resistance	11 mΩ
Capacity ranking	#9 of 15 26650s	Max continuous discharge	32 A (mooch)
		Discharge C-rate	7.6C
		Standard charge current	2,000 mA
		Typical charge time	2.1 h

C-RATE CONVERSION · 4,200 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.84 A	5h 00m
0.5C	2.1 A	2h 00m
1C	4.2 A	1h 00m
2C	8.4 A	30m
3C	12.6 A	20m
5C	21 A	12m
8C	33.6 A	7m 30s

Highlighted row is closest to the rated 32 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
------	---------	------------------------

Standard	2,000 mA	~2h 06m
0.5C	2,100 mA	~2h 00m
1C	4,200 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	12.6 Ah	136 Wh
7S	25.2 V	29.4 V	21	12.6 Ah	318 Wh
10S	36 V	42 V	30	12.6 Ah	454 Wh
13S	46.8 V	54.6 V	39	12.6 Ah	590 Wh
14S	50.4 V	58.8 V	42	12.6 Ah	635 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 8,400 mAh · 212 Wh 64 A max · ~1.33 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 16,800 mAh · 786 Wh 128 A max · ~4.94 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 16,800 mAh · 968 Wh 128 A max · ~6.08 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 25,200 mAh · 363 Wh 192 A max · ~2.28 kg cells
---	--	---	---

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Vapcell 26650 4200mAh 32A (this cell)	4,200	32 A	15.12	95 g	159
Hohm Tech HOHMGROWN	4,307	32 A	15.5	88.8 g	175

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.

- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/vapcell-26650-4200mah-32a
Manufacturer datasheet	https://www.vapcelltech.com/h-pd-57.html
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-v...
Full cell database	cellsaviors.com/cell-database