

Illustrative render generated from published specifications

18.3 × 65 mm
50 g

Vapcell BLACK

25A 2800mAh



Live page & updates

Vapcell · released 2018

18650 NMC

MOOCH-TESTED · 25 A

2,800 mAh CAPACITY	25 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	10.08 Wh ENERGY · 201.6 WH/KG
--	---	---	---

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S #77 of 279 Lowest in databaseHighest Higher discharge than 84% of 18650 cells in our database. Great for high-drain builds.	VOLTAGE OPERATING WINDOW 1.7 V usable Cutoff 2.5 VNominal 3.6 VMax 4.2 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
--	--

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Enough discharge to handle amplifier bursts without voltage sag.
High-drain vaping	Above the 25A Mooch CDR threshold. Suitable for regulated and mechanical mods.
Flashlights	Decent runtime. Works well for most flashlights.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY

Manufacturer	Vapcell
Model	BLACK 25A 2800mAh
Format	18650
Chemistry	NMC
Year released	2018
Wrap colour	■ Black
Terminal	Flat top
Protection	Unprotected

ENERGY & POWER DENSITY

Energy	10.08 Wh
Specific energy	201.6 Wh/kg
Volumetric density	589.6 Wh/L
Power density (mass)	1,800 W/kg
Power density (volume)	5,264 W/L
Capacity ranking	#77 of 279 18650s

PHYSICAL

Diameter	18.3 mm
Length	65 mm
Weight	50 g

ELECTRICAL

Rated capacity	2,800 mAh
Nominal voltage	3.6 V
Max charge voltage	4.2 V
Discharge cutoff	2.5 V
Energy	10.08 Wh
Internal resistance	12 mΩ
Max continuous discharge	25 A (mooch)
Discharge C-rate	8.9C
Standard charge current	2,000 mA
Typical charge time	1.4 h
Standard discharge	560mA

C-RATE CONVERSION · 2,800 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.56 A	5h 00m
0.5C	1.4 A	2h 00m
1C	2.8 A	1h 00m
2C	5.6 A	30m
3C	8.4 A	20m
5C	14 A	12m
8C	22.4 A	7m 30s

Highlighted row is closest to the rated 25 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
------	---------	------------------------

0.5C	1,400 mA	~2h 00m
Standard	2,000 mA	~1h 24m
1C	2,800 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	8.4 Ah	91 Wh
7S	25.2 V	29.4 V	21	8.4 Ah	212 Wh
10S	36 V	42 V	30	8.4 Ah	302 Wh
13S	46.8 V	54.6 V	39	8.4 Ah	393 Wh
14S	50.4 V	58.8 V	42	8.4 Ah	423 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 5,600 mAh · 141 Wh 50 A max · ≈0.7 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 11,200 mAh · 524 Wh 100 A max · ≈2.6 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 11,200 mAh · 645 Wh 100 A max · ≈3.2 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 16,800 mAh · 242 Wh 150 A max · ≈1.2 kg cells
--	---	--	--

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Vapcell BLACK 25A 2800mAh (this cell)	2,800	25 A	10.08	50 g	202
LG LGABE11865	3,200	9 A	12	49 g	245
LG LGEBE11865	3,200	4.9 A	12	49 g	245
Samsung ICR18650-32A	3,200	6.4 A	12	50 g	240
Sanyo NCR18650GA	3,300	10 A	11.9	48 g	248
EVE EVE-INR18650/33V	3,200	10 A	11.5	48 g	240

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/vapcell-black-25a-2800mah
Manufacturer datasheet	https://www.vapcelltech.com/h-pd-83.html
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-v...
Full cell database	cellsaviors.com/cell-database