

Illustrative render generated from published specifications

21.6 × 71 mm
74 g

Vapcell F56

Vapcell · released 2023

21700

NMC

MOOCH-TESTED · 12 A




Live page & updates

5,600 mAh CAPACITY	12 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	20.16 Wh ENERGY · 272.43 WH/KG
--	---	---	--

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.



APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Might work for smaller setups. Check your amp's peak current draw.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	May work for lighter-duty tools. Check your tool's current requirements.

IDENTITY

Manufacturer	Vapcell
Model	F56
Format	21700
Chemistry	NMC
Year released	2023
Wrap colour	Gold
Terminal	Flat top
Protection	Unprotected

OPERATING TEMPERATURE

Discharging	-20°C to 60°C
-------------	---------------

ENERGY & POWER DENSITY

Energy	20.16 Wh
Specific energy	272.43 Wh/kg
Volumetric density	774.88 Wh/L
Power density (mass)	584 W/kg
Power density (volume)	1,660 W/L
Capacity ranking	#12 of 72 21700s

PHYSICAL

Diameter	21.6 mm
Length	71 mm
Weight	74 g

ELECTRICAL

Rated capacity	5,600 mAh
Nominal voltage	3.6 V
Max charge voltage	4.2 V
Discharge cutoff	2.5 V
Energy	20.16 Wh
Internal resistance	16 mΩ
Max continuous discharge	12 A (mooch)
Discharge C-rate	2.1C
Standard charge current	2,000 mA
Typical charge time	2.8 h
Cycle life	1,000 cycles

C-RATE CONVERSION · 5,600 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	1.12 A	5h 00m
0.5C	2.8 A	2h 00m
1C	5.6 A	1h 00m
2C	11.2 A	30m

Highlighted row is closest to the rated 12 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
------	---------	------------------------

Standard	2,000 mA	~2h 48m
0.5C	2,800 mA	~2h 00m
1C	5,600 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	16.8 Ah	181 Wh
7S	25.2 V	29.4 V	21	16.8 Ah	423 Wh
10S	36 V	42 V	30	16.8 Ah	605 Wh
13S	46.8 V	54.6 V	39	16.8 Ah	786 Wh
14S	50.4 V	58.8 V	42	16.8 Ah	847 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 11,200 mAh · 282 Wh 24 A max · ~1.04 kg cells	13S4P 48V ebike standard 52 cells · 46.8 V 22,400 mAh · 1,048 Wh 48 A max · ~3.85 kg cells	16S4P DIY powerwall 64 cells · 57.6 V 22,400 mAh · 1,290 Wh 48 A max · ~4.74 kg cells	4S6P Power tool replacement 24 cells · 14.4 V 33,600 mAh · 484 Wh 72 A max · ~1.78 kg cells
--	---	--	--

SIMILAR CELLS

Same format and chemistry, within ±500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Vapcell F56 (this cell)	5,600	12 A	20.16	74 g	272
Linkdata 60P	6,000	60 A	21.6	68 g	318
Vapcell F60	6,000	12 A	21.6	74 g	292
Reliance RH60	5,850	20 A	21.1	71 g	297
Reliance RS60	5,850	50 A	21.1	71.5 g	295
Lishen LR2170SK	5,800	16 A	20.9	—	—

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.
- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/vapcell-f56
Manufacturer datasheet	https://www.vapcelltech.com/h-pd-189.html
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-v...
Full cell database	cellsaviors.com/cell-database