

Illustrative render generated from published specifications

21.6 × 71 mm

Vapcell F63

Vapcell

21700

NMC

MOOCH-TESTED · 12 A



Live page & updates

6,250 mAh CAPACITY	12 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	22.5 Wh ENERGY
--	---	---	--------------------------------------

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 21700S

#4 of 72

Lowest in database

Highest

More capacity than 96% of 21700 cells in our database, but lower discharge than average.

VOLTAGE OPERATING WINDOW

1.7 V usable

Cutoff 2.5 V

Nominal 3.6 V

Max 4.2 V

Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	High capacity means more stored energy per cell. Fewer cells needed for a given kWh target.
Ebike packs	Good balance of capacity for range and discharge for hills. Works well in most ebike packs.
Car audio	Might work for smaller setups. Check your amp's peak current draw.
High-drain vaping	Below the 25A Mooch CDR threshold that high-drain vaping needs. Use a higher-drain cell.
Flashlights	High capacity means long runtime. Great for everyday carry and extended use.
Power tools	May work for lighter-duty tools. Check your tool's current requirements.

IDENTITY		PHYSICAL		
Manufacturer	Vapcell	Diameter	21.6 mm	
Model	F63	Length	71 mm	
Format	21700	ELECTRICAL		
Chemistry	NMC			
Wrap colour	 Gold		Rated capacity	6,250 mAh
Terminal	Flat top		Nominal voltage	3.6 V
Protection	Unprotected		Max charge voltage	4.2 V
ENERGY & POWER DENSITY			Discharge cutoff	2.5 V
			Energy	22.5 Wh
Energy	22.5 Wh	Internal resistance	20 mΩ	
Volumetric density	864.82 Wh/L	Max continuous discharge	12 A (mooch)	
Power density (volume)	1,660 W/L	Discharge C-rate	1.9C	
Capacity ranking	#4 of 72 21700s	Standard charge current	2,000 mA	
		Typical charge time	3.1 h	

C-RATE CONVERSION · 6,250 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	1.25 A	5h 00m
0.5C	3.13 A	2h 00m
1C	6.25 A	1h 00m
2C	12.5 A	30m

Highlighted row is closest to the rated 12 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
Standard	2,000 mA	~3h 08m
0.5C	3,125 mA	~2h 00m
1C	6,250 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	18.8 Ah	203 Wh
7S	25.2 V	29.4 V	21	18.8 Ah	472 Wh
10S	36 V	42 V	30	18.8 Ah	675 Wh
13S	46.8 V	54.6 V	39	18.8 Ah	878 Wh
14S	50.4 V	58.8 V	42	18.8 Ah	945 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 12,500 mAh · 315 Wh 24 A max	13S4P 48V ebike standard 52 cells · 46.8 V 25,000 mAh · 1,170 Wh 48 A max	16S4P DIY powerwall 64 cells · 57.6 V 25,000 mAh · 1,440 Wh 48 A max	4S6P Power tool replacement 24 cells · 14.4 V 37,500 mAh · 540 Wh 72 A max
---	--	---	---

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Vapcell F63 (this cell)	6,250	12 A	22.5	—	—
Amprius INR21700-65	6,500	13 A	23.4	74 g	316
BAK 65E	6,500	25 A	23.4	—	—
Linkdata 65P	6,500	52 A	23.4	70.2 g	333
Linkdata 60P	6,000	60 A	21.6	68 g	318
Vapcell F60	6,000	12 A	21.6	74 g	292

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.

- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/vapcell-f63
Manufacturer datasheet	https://akkutests.de/test-vapcell-f63.html
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/bench-test-results-v...
Full cell database	cellsaviors.com/cell-database