

Illustrative render generated from published specifications

Xtar XTVTC4

Xtar · released 2016

18650 LMO

MOOCH-TESTED · 25 A



Live page & updates

2,200 mAh CAPACITY	25 A MOOCH CONTINUOUS	3.6 V NOMINAL · 2.5 – 4.2 V	7.92 Wh ENERGY
--	---	---	--------------------------------------

REFERENCE ONLY — NOT AN OFFICIAL DOCUMENT

This information is gathered from multiple sources, including manufacturer datasheets, independent third-party testing, and community contributions. Cell specifications vary between production batches and change over time, and no figure here is guaranteed to be correct or current. **Always consult the manufacturer's spec sheet directly.** Use this sheet for reference only — never as the sole basis for a safety-critical decision about charging, discharging, or assembling cells. The cell image is an illustrative render generated from published specifications, not a photograph.

CAPACITY AMONG 18650S #170 of 279 Lowest in databaseHighest Higher discharge than 84% of 18650 cells in our database. Great for high-drain builds.	VOLTAGE OPERATING WINDOW 1.7 V usable Cutoff 2.5 VNominal 3.6 VMax 4.2 V Below nominal the cell sags fast under load; above it, the last of the capacity fills slowly on the constant-voltage taper.
--	---

APPLICATION SUITABILITY

Rule-of-thumb ratings from this cell's capacity and continuous discharge. Check your own load before committing.

Powerwalls	Usable for powerwalls but lower capacity means you'll need more cells to hit your target kWh.
Ebike packs	Marginal. Check your motor's peak draw first. You might get voltage sag under load.
Car audio	Enough discharge to handle amplifier bursts without voltage sag.
High-drain vaping	Above the 25A Mooch CDR threshold. Suitable for regulated and mechanical mods.
Flashlights	Lower capacity means shorter runtime. Better cells are available for flashlight use.
Power tools	Sufficient discharge and capacity for most power tool packs.

IDENTITY		ELECTRICAL	
Manufacturer	Xtar	Rated capacity	2,200 mAh
Model	XTVTC4	Nominal voltage	3.6 V
Format	18650	Max charge voltage	4.2 V
Chemistry	LMO	Discharge cutoff	2.5 V
Year released	2016	Energy	7.92 Wh
Terminal	Flat top	Max continuous discharge	25 A (mooch)
Protection	Unprotected	Discharge C-rate	11.4C
ENERGY & POWER DENSITY		Standard charge current	1,000 mA
Energy	7.92 Wh	Typical charge time	2.2 h
Capacity ranking	#170 of 279 18650s		

C-RATE CONVERSION · 2,200 MAH

C-RATE	CURRENT	THEORETICAL RUNTIME
0.2C	0.44 A	5h 00m
0.5C	1.1 A	2h 00m
1C	2.2 A	1h 00m
2C	4.4 A	30m
3C	6.6 A	20m
5C	11 A	12m
8C	17.6 A	7m 30s
10C	22 A	6m

Highlighted row is closest to the rated 25 A continuous discharge.

CHARGING

RATE	CURRENT	ESTIMATED TIME TO FULL
Standard	1,000 mA	~2h 12m
0.5C	1,100 mA	~2h 00m
1C	2,200 mA	~1h 00m

Constant-current phase only. Real charge time runs longer because of the constant-voltage taper at the end.

SERIES PACK CONFIGURATIONS

Voltages calculated from this cell's own nominal and maximum charge voltage. The 3P columns show one common parallel count as a worked example — scale the parallel group to the capacity you need.

SERIES	NOMINAL	FULLY CHARGED	CELLS AT 3P	CAPACITY	ENERGY
3S	10.8 V	12.6 V	9	6.6 Ah	71 Wh
7S	25.2 V	29.4 V	21	6.6 Ah	166 Wh
10S	36 V	42 V	30	6.6 Ah	238 Wh
13S	46.8 V	54.6 V	39	6.6 Ah	309 Wh
14S	50.4 V	58.8 V	42	6.6 Ah	333 Wh

EXAMPLE PACKS

7S2P 24V ebike / small pack 14 cells · 25.2 V 4,400 mAh · 111 Wh 50 A max	13S4P 48V ebike standard 52 cells · 46.8 V 8,800 mAh · 412 Wh 100 A max	16S4P DIY powerwall 64 cells · 57.6 V 8,800 mAh · 507 Wh 100 A max	4S6P Power tool replacement 24 cells · 14.4 V 13,200 mAh · 190 Wh 150 A max
--	--	---	--

SIMILAR CELLS

Same format and chemistry, within ± 500 mAh.

CELL	MAH	CONTINUOUS	WH	WEIGHT	WH/KG
Xtar XTVTC4 (this cell)	2,200	25 A	7.92	—	—
AWT 40A 2600mAh	2,600	40 A	9.4	—	—
AWT YELLOW 40A 2600mAh	2,600	40 A	9.4	—	—
Golisi S26	2,600	25 A	9.4	46 g	203
Efest 18650 2100mAh 38A	2,100	38 A	7.6	—	—
Efest PURPLE 30A 2100mAh	2,100	30 A	7.6	—	—

HANDLING & SAFETY

- Never charge above 4.2V or discharge below 2.5V.
- Store cells at around 3.6-3.8V (roughly 40-60% charge) for long-term storage.
- Don't mix cells with different capacities, chemistries, or states of charge in a pack.
- Inspect wraps before use. A torn wrap can cause a short circuit.

- Always use a BMS or balance charger appropriate for your pack configuration.
- Keep cells away from metal objects, keys, and coins. A short across the terminals can cause fire.

SOURCES & FURTHER READING

Cell Saviors page	cellsaviors.com/cell-database/xtar-xtvtc4
Independent test (Mooch)	https://www.e-cigarette-forum.com/threads/xtar-xtvtc4-25a-2200...
Full cell database	cellsaviors.com/cell-database